



D5111-1 BRACKET

- NOTES:**
- 1) MATERIAL: 7075-T6 (OR T651/T6510/T6511/T62) ALUMINUM BAR
PER AMS-QQ-A-225/9 (OR AMS 4122/4123/4186/4187)
OR PER AMS-QQ-A-200/11
REF DART SPEC M7075T6B
 - 2) FINISH: HARD ANODIZE IAW MIL-A-8625 TYPE III, CLASS 2, COLOR BLACK,
PRIME IAW MIL-P23377J TYPE I CLASS N; 1-2 MIL MAX, AS PER QSI 005.
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D5111-1", REVISION, BATCH NUMBER AND
DATE OF MANUFACTURE, USING AN X-TENSION STAMP, PER QSI 044 METHOD 6.2
 - 7) WEIGHT: 0.03 lbs (0.013 kgs)

APPROVED

B	REVISE NOTE 6) (ZN A8-1)	AK	14.06.05
A	NEW ISSUE	AK	14.04.30
REV.	DESCRIPTION	BY	DATE
DESIGN	AK	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	HS	DRAWING NO. REV. B	
MFG. APPR.	JLM	D5111 SHEET 1 OF 1	
APPROVED	HS	TITLE SCALE	
DE APPR.	DS	BRACKET NTS	
DATE	14.06.05	<small>COPYRIGHT © 2014 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	

RELEASED
2014-06-11
MP